



Clifton Cameras Product Specification

Sony HVL-F28RM Flashgun Full Spec

Basic information

DIMENSIONS (APPROX.)

W 65.1mm X H 83.5mm X D 91.4mm (2 5/8inches × 3 3/8inches × 3 5/8inches)

WEIGHT(APPROX.)

219g (7.8 oz) (only main unit)

Type

TYPE

Auto electronic flash (clip-on type) with pre-flash metering

SHOE TYPE

Multi Interface Shoe.

Flash Head(Light-emitting unit)

MAXIMUM GUIDE NUMBER

28 (Flash coverage setting 50mm, ISO100 · m)

FLASH COVERAGE

50mm, Angle of view at 24mm focal length is also covered with the wide panel

FLASH MODE

TTL/MANUAL/MULTI

FLASH DURATION (APPROX.)

Within 1.6ms (1/1 MANUAL)

COLOR TEMPERATURE (APPROX.)

5500K

FREQUENCY (APPROX.)



0.1-6.4 seconds(Alkaline battery)/0.1-4.1 seconds(Ni-MH battery) ²

REPETITION (APPROX.)

More than 110 times(Alkaline battery)/More than 130 times(Ni-MH battery) ³

CONTINUOUS FLASH PERFORMANCE

40 flashes at 10 flashes per second ⁴

BOUNCE FLASH

Yes

BOUNCE ANGLE

Up 120deg (0deg/20deg/40deg/60deg/80deg/120deg)

TEST FLASH

Yes

FLASH CONTROL

Flash control using pre-flash (P-TTL/ADI)

FLASH COMPENSATION

Yes ⁵

POWER LEVEL SWITCHING

25 levels (1/1-1/256) 1/3 steps

HIGH-SPEED SYNC(HSS)

Yes

MODELING FLASH

Yes

BUILT-IN WIDE PANEL

Yes (24mm)

BUILT-IN BOUNCE SHEET

Yes

AF illuminator

AF ILLUMINATOR

-

OPERATING RANGE (APPROX.)

-

Radio controlled wireless function

RADIO CONTROL WIRELESS FUNCTION

Yes (commander/receiver) ⁶

FREQUENCIES

2.4 GHz band

CHANNELS

14 Channels (Auto/manual)

COMMUNICATION DISTANCE (APPROX.)

35m ⁷⁸

GROUPS

3 groups (TTL/MANUAL),5 groups (group flash photography)

MAXIMUM FLASH UNITS

15 units

LIGHTING RATIO CONTROL

3 groups (TTL)

Optical control wireless function

OPTICAL CONTROLLED WIRELESS FLASH

-

CHANNELS

-

COMMUNICATION DISTANCE (APPROX.)

- ⁸



GROUPS

-

LIGHTING RATIO CONTROL

-

LED light function

CENTER LUMINANCE INTENSITY (APPROX.)

-

LIGHTING DISTANCE (APPROX.)

-

FOCAL LENGTH SUPPORTED

-

CONTINUOUS LIGHTING TIME (APPROX.)

-

COLOR TEMPERATURE (APPROX.)

-

POWER LEVEL SWITCHING

-

Other functions

AUTO ZOOM CONTROL OPTIMIZED FOR IMAGE SENSOR SIZE

-

FLASH DISTRIBUTION SETTING

-

AUTO WB ADJUSTMENT

Yes⁹

CUSTOM KEY SETTINGS

-



MEMORY SETTINGS

Yes

REMOTE RELEASE

-

Display

LCD PANEL

-

CHARGE PROGRESS INDICATOR

-

External connectors

SYNC TERMINAL

-

MULTI/MICRO USB TERMINAL

Yes

Power source

POWER SOURCE

Four AA-size alkaline or Ni-MH batteries

EXTERNAL BATTERY ADAPTOR

-

Other features

DUST AND MOISTURE RESISTANT DESIGN

Yes¹⁰

What's In The Box

Connector protect cap(1), Mini-stand(1), Carrying pouch (1), Dust and moisture resistant cover

(1)