



Clifton Cameras Product Specification

Canon RF 1200mm f8L IS USM Lens Full Spec

OPTICAL FEATURES / SPECIFICATIONS	
Image size	Full Frame
Angle of view (horzntl, vertl, diagnl)	01°45', 01°10', 02°05'
Lens Construction (Elements/Groups)	26/18
Special Optics	2x Fluorite, 1X SUD, 1x UD
No. of diaphragm blades	9
Minimum Aperture	64
Closest Focusing Distance (m)	4.3
Maximum Magnification (x)	0.29
Control Ring	via Focus ring
Image Stabilizer OIS1	4
Image Stabilizer IBIS x OIS1	4
AF Actuator	Ring USM
Coatings	ASC, Super Spectra
Fluorine	Front
PHYSICAL SPECIFICATIONS	
Dust/moisture resistance²	Yes
Exterior coating	Heat Shield
Filter diameter (mm)	52
Max. diameter x length (mm)	168 x 537
Weight (g)	3340
ACCESSORIES	
Lens Cap	E-185C
Lens Hood	ET-160 (WIII)
Lens Case/Pouch	Lens Soft Case LS1200
Rear cap	Lens Dust Cap RF



Extender Compatibility	Compatible with RF Extender only
Other Accessories	Canon drop-in 52mm filters Canon Drop-In Circular Polarizing Filter 52 (WIII) Canon Lens Short Hood ET-1 60B