

Clifton Cameras Product Specification

Rode VideoMicro II

Specifications

Acoustic & Electrical

| | |
|------------------------|---|
| Acoustic Principle: | Pressure Gradient. Electret Condenser |
| Polar Pattern: | Supercardioid |
| Frequency Response: | 20Hz – 20kHz |
| Output Impedance: | ~2.6k Ω |
| Signal-to-Noise Ratio: | 79 dB |
| Dynamic Range: | 95 dB |
| Sensitivity: | -30dBV (31.62 mV @ 94 dB SPL) \pm 1 dB @ 1kHz |
| Max SPL: | 110 dB SPL |
| Output Connection: | 3.5mm TRS |

Mechanical

| | |
|---------------------------|--|
| Weight (grams): | VideoMicro II: 24 |
| | VideoMicro II with isolation mount: 39 |
| Dimensions (millimeters): | Length: 80 |
| | Diameter: 22 |
| Included Accessories: | <ul style="list-style-type: none">• Helix™ Isolation Mount• Foam Windshield• WS12 Furry Windshield• SC7 TRS to TRRS Patch Cable• SC13 TRS to TRS Patch Cable |
| Compatible Accessories: | <ul style="list-style-type: none">• SC3• SC4• SC8• SC11 |



- DCS-1
- Tripod 2
- VXLR Pro
- VXLR+
- Mini Boompole