



Spypoint FLEX E-36 Specification

[Spypoint FLEX E-36](#)

Specifications

Network:	LTE Multi-carrier auto connectivity
Transmission Plan:	Transmission of your photos and videos to your SPYPOINT application by cellular network. Visit www.spypoint.com/plans to choose a plan that suits you.
Camera Configuration:	Fully configurable remotely with the free SPYPOINT app.
Detection Range:	Up to 30 m (100 ft)
Detection Angle:	50°
Motion Detector:	Infrared sensor
Trigger Speed:	0.5 s
Photo Resolution:	36 MP
Photo Format:	.jpg
Time Lapse Mode:	Time-Lapse and Time-lapse+ (Time-lapse with motion detection enabled)
Multishot Mode:	Up to 3 photos per detection
Information appearing on photos only:	Date, time, temperature (°C/°F), moon phase, Spypoint logo, and camera model
Capture Mode:	Colour by day, black and white by night
Delay Between Each Detection:	Adjustable from instant to 30 minutes
External Memory:	microSD card up to 512 GB (not included)
Power Source(s):	8 x AA batteries (not included) Lithium battery pack (LIT-22) (not included) Solar panel lithium battery #SPLB-22 (not included) External 12 V battery (not included) Optional accessories available at SPYPOINT: KIT6V-12V, KIT-12V, BATT-12V
Illumination Options:	4 powerful LED
Night Light Range:	Up to 30 m (100 ft)
Dimensions:	10.67x13x7.88 cm (H,W,D)



Operating Temperatures: -30 to +50 °C