



Clifton Cameras Product Specification

Canon RF 50mm F1.4L VCM Lens Full Spec

Focal Length – 50mm

AF Type - Nano USM and VCM[2]

Image Stabilizer - No

Diaphragm Blades - 11

Special Optics - 2 x Aspherical 1 x UD

Coatings - ASC, Super Spectra

Fluorine – Yes (front)

Minimum Aperture – f/16

Closest Focusing Distance – 0.40m

Maximum Magnification – 0.15x

Dust & Moisture Resistance[3] - Yes

Filter Type – 67mm

Dimensions (Diameter x Length)[4] - 76.5x 99.3 mm

Weight – 580g

1. Various limitations apply to some cameras; we recommend installing the latest Firmware update on your camera for best performance. Even with latest Firmware update on EOS R, RP, Ra, R3, R5, R6, R6 Mark II, R7, R8, R10, R50, R100 and EOS R5C when shooting still photos, the aperture value cannot be set using the iris ring.

2. The Voice Coil Motor in the lens emits a low-level magnetic field. While generally safe to use, we advise consulting your doctor if you have a pacemaker or any other medical device to address any concerns.

3. Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

4. Lens dimensions when in retracted state.