

# **Clifton Cameras Product Specification**

## Canon imagePROGRAF PRO-1100 Inkjet Printer Full Spec

Class 17"

Ink Type 12 Inks: MBK/PBK/C/M/Y/PC/PM/GY/PGY/R/B/CO

Maximum Print Resolution [1] 2,400 x 1,200 dpi

Printing Speed [2] A2 (LU-101 colour): Approx.3mins 40s A2 (PT-101 colour or mono): Approx. 6mins

**Dimensions, Weight** Approx. 723 x 435 x 285 mm Weight approx. 32.4kg (including print head and inks)

Power Supply AC 100-240V(50-60Hz)

Power Consumption Printing (Approx. 38W)  $^{[3]}$  Standby (Sleep) (Approx. 1.2W) OFF (Approx. 0.1W)

**Operational Environment** Sleep mode (Erp Lot26) Approx. 2.3W Temperature: 5-35°C, Humidity: 10-90%RH (no dew condensation) [4]

Acoustic Noise approx. 42.5 dB(A) - Plain Paper(A4, Color) [5] approx. 43.0 dB(A) - Photo Paper Pro Platinum (PT-201) (4×6, Color, borderless) [6]

Operation Panel Display 3.0" (320 x 240 TFT LCD), Key x 9, LED x 2

22 Languages Selectable: Japanese/English/German/Italian/Spanish/Brazilian Portuguese/Dutch/Polish/Russian/French/Simplified Chinese/Traditional Chinese/Korean/Thai/Indonesian/Turkish Czech/Danish/Swedish/Norwegian/Finnish/Ukrainian

Memory 1GB

INTERFACE TYPE & SOFTWARE

Supported Operating Systems <sup>[7]</sup> Windows 7 SP1, Windows 8.1, Windows 10, Windows 11 Windows Server 2008 R2 SP1, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Windows Server 2022

Mac OS OS11.7.10 - OS14

Supported Mobile Systems Chrome OS iOS Android

Interface USB B Port: Hi Speed USB Protocol SNMP, HTTP, TCP/IP(IPv4/IPv6)

Supported Standards: IEEE802.3ab (1000BASE-T) / IEEE802.3u (100BASE-TX) / IEEE802.3 (10BASE-T)

Transfer speed: 10Mbps / 100Mbps / 1000Mbps (Auto switching)

Security: IEEE802.1X(EAP-TLS/EAP-TTLS/PEAP)

Wireless LAN Supported Standards: IEEE802.11n / IEEE802.11g / IEEE802.11b / IEEE802.11a / IEEE802.11ac

2.4GHz Channel EUM / EMB

5GHz Channel GB ONLY

ends on the transmission speed and conditions



Security WPA-PSK(AES) WPA2-PSK(AES) WPA3-SAE(AES) WPA-FAP(AES)\* WPA2-FAP(AES)\* WPA3-FAP(AES)\*

\* IEEE802.1X(EAP-TLS/EAP-TTLS/PEAP) available

Direct Connection (Wireless Direct) Available

Smart device & Cloud apps Canon PRINT app (iOS or Android) Cloud Link Apple AirPrint Mopria for Android

Camera direct Wi-Fi Pictbridge

Software Professional Print & Layout

PRINT HEAD Type Canon Bubble-jet on Demand Head Configuration 12 colors integrated type (4 colors chips x 3) Nozzle Pitch 600dpi x 2 lines

INK TANK
Model LUCIA PRO II Ink Tanks: PFI-4100 MBK/ PBK/C/M/Y/PC/PM/GY/PGY/R/B/CO

# Page yield (4x6" PT-101) [8] Number of 10x15cm photos

Matte Black (MBK): 6070 photos\* Photo Black (PBK): 2220 photos\* Grey (GY): 1870 photos\* Photo Grey (PGY): 3685 photos\* Photo Cyan (PC): 4785 photos\* Cyan (C): 5420 photos\* Photo Magenta (PM): 4050 photos Magenta (M): 4735 photos\* Yellow (Y): 3415 photos Red (R): 5675 photos\* Blue (B): 5580 photos\* Chroma Optimizer (CO): 925 photos \* Estimated Supplemental Yield

## Page yield (A2 PT-101) [8]

Number of A2 colour photos

Matte Black (MBK): 1315 photos\* Photo Black (PBK): 206 photos\* Grey (GY): 133 photos\*

Photo Grey (PGY): 348 photos\* Photo Cyan (PC): 555 photos\* Cyan (C): 700 photos\*

Photo Magenta (PM): 404 photos\* Magenta (M): 905 photos\* Yellow (Y): 320 photos Red (R): 760 photos\* Blue (B): 805 photos\*
Chroma Optimizer (CO): 90 photos\* \* Estimated Supplemental Yield

### MEDIA HANDLING

 $\begin{array}{l} \textbf{Top Tray} \\ \textbf{A5, A4, A3, A3+, A2, B5, B4, B3, Letter, Legal, 89 x 127mm (L), 210 x 594mm, KG / 4" X 6" (10 x 15cm), 2L / 5" X 7" (13 x 18cm), 7" X 10" (18 x 25cm), 8" X 10" (20 x 25cm), 9 X 13" (23 x 33cm), 10" X 12" (25 x 30cm), 11" X 14", 11" x 17" (28x443cm), 12" X 12" (30 x 30cm), 13" X 19" (Super B), 14" X 17" (36 x 43cm), 16" x 20",17" x 22" (43 x 56cm), 17" X 25" (43 x 64cm). \end{array}$ 

Manual Feed Tray

A4, A3, A3+, A2, B4, B3, Letter, Legal, 210 x 594mm, 8" X 10" (20 x 25cm), 9 X 13" (23 x 33cm), 10" X 12" (25 x 30cm), 11" X 14", 11" x 17" (28x443cm), 12" X 12" (30 x 30cm), 13" X 19" (Super B), 14" X 17" (36 x 43cm), 16" x 20", 17" x 22" (43 x 56cm), 17" X 25" (43 x 64cm).

### Paper Size (Borderless)

A4, A3, A3+, A2, B4, B3, Letter, Legal, 210 x 594mm, 8" X 10" (20 x 25cm), 10" X 12" (25 x 30cm), 13" X 19" (Super B), 14" X 17" (36 x 43cm), 17" x 22" (43 x 56cm), 17" X 25" (43 x 64cm).

Supported Media (Top Tray)
Plain Paper, Photo Paper Pro Platinum (PT-101), /Photo Paper Pro Luster (LU-101), Photo Paper Plus Glossy II (PP-201), /Matte Photo Paper (MP-101), Photo Paper Plus Semi-gloss (SG-201), Lightweight Photo Paper, Heavyweight Fine Art Paper, Japanese Paper Washi, Canvas,

Supported Media (Manual Feed Tray)
Photo Paper Pro Platinum (PT-101), Photo Paper Pro Luster (LU-101), Photo Paper Plus Glossy II (PP-201), Matte Photo Paper (MP-101)/ Photo Paper Plus Semi-gloss( SG-201), Premium Fine Art Rough (FA-RG1), Premium Fine Art Smooth (FA-SM1), Lightweight Photo Paper, Heavyweight Photo Paper, Heavyweight Fine Art Paper, Extra Heavyweight Fine Art Paper, Japanese Paper Washi, Canvas, Baryta Photo Paper

### Media Thickness

Top Tray: Plain paper 64-105g/m<sup>2</sup>, Canon specialty paper Max. 300g/m<sup>2</sup>, Top Tray: Thickness: 0.1-0.3mm Manual Feed Tray: Canon specialty paper Max. 400g/m², Manual Tray Thickness: 0.1-0.7mm



Media Width Top Tray: 89-432mm, Manual feed slot: 203.2-432mm

Minimal Printable Paper Length Top Tray: 127mm, Manual Feed Tray: 254mm

Maximum Printable Paper Length 3276.70mm

### MARGINS (TOP, BOTTOMS, SIDES)

Recommended - Top margin: 57mm, Bottom margin: 55mm, Left/Right: 3.4mm (LTR/LGL: Left margin 6.4mm, Right margin 6.3mm) Printable area -Top margin 3mm, Bottom margin 5mm, Left/Right margin 3.4mm (LTR/LGL: Left margin 6.4mm, Right margin 6.3mm)

(LTR/LGL: Left margin 6.4mm, Right margin 6.3mm)

Media Width for Borderless Printing <sup>[9]</sup> A4, A3, A3+, A2, 4x6", 5x7", 8x10", 10x12", 14x17", 17x22", LTR

CONSUMABLES Ink Tank PFI-4100 MBK/PBK/C/M/Y/PC/PM/GY/PGY/R/B/CO (80ml)

Maintenance Cartridge MC-20

### **Disclaimers**

- 1. [1] Ink droplets can be placed with a pitch of 1/2400 inch at minimum.
- 2. [2] Print speed is based on the default setting using ISO/JIS-SCIDN5anddoesnottakeinto

account data processing time on the host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

- 3. [3] When printing ISO/JIS-SCIDN2patternonA4sizePhotoPaperProPlatinum(PT-101)using default settings.
- 4. [4] The performance of the printer may be reduced under certain temperature and humidity conditions.
- 5. [5] When printingISO/JIS-SCIDN2patternonPhotoPaperProPlatinumusingdefaultsettings.
- 6. [6] Acoustic Noise is measured based on ISO7779 standard.
- 7. [7] Minimum system requirements is according to that of OS and application software used.
- 8. [8] Declared yield value in accordance with ISO/IEC29103. Values obtained by continuous printing.
- 9. [9] Paper types NOT supported for borderless printing are as follows: Photo Stickers

Specifications are subject to change without notice.