

Clifton Cameras Product Specification

Fujifilm Instax Wide 400 camera Full Spec

Specifications

Film	FUJIFILM instax™ WIDE FILM
Photo Picture Size	62 mm × 99 mm
Lens	Retractable lens, 2 components, 2 elements, f= 95 mm, 1:14
Viewfinder	Real image finder, 0.37x, with target spot
Shooting Range	Manual 2-range switching (0.9 m – 3 m/3 mand beyond) Normal Mode (0.9 m - 3 m)Landscape Mode (3 m and beyond)
Shutter	Programmed electronic shutter release, 1/64 sec – 1/200 sec.
Exposure Control	Automatic Lv 10.5 to 15 (ISO 800)
Film Ejection	Automatic
Film Developing Time	Approx. 90 seconds (varies depending on the ambient temperature)
Flash	Built-in, automatic electronic flash (automatic light adjustment), Recycle time: 7 seconds or less (when using new batteries), Effective flash range: 0.9 to 3 m
Power Supply	Four AA-size alkaline batteries (LR6), Capacity: approx. 10 instax™ WIDE film cartridges of 10 exposures each (depends on usage conditions) * The supplied batteries are for trial use. When they run out, replace them with new ones (alkaline batteries). The performance of alkaline batteries varies depending on the brand.* Manganese batteries cannot be used.
Auto Power Off Time	After 5 minutes
Others	Film counter, film cartridge confirmation window, tripod socket (tripod sold separately).
Dimensions	162 mm × 98 mm × 123 mm
Weight	616 g (without battery, strap, film cartridge, and close-up lens)

The above specifications are subject to change for performance improvement.