

Clifton Cameras Product Specification

Panasonic LUMIX S 18-40mm F4.5-6.3 Lens Full Spec

LUMIX S 18-40mm F4.5-6.3	
Lens Construction	8 elements in 7 groups (3 aspherical lenses, 2 ED lenses, 1 UHR lens) (excluding 1 protection element)
Mount	L-Mount
Optical Image Stabilizer	-
Focal Length	f=18-40mm
Aperture Type	7 diaphragm blades / Circular aperture diaphragm
Maximum Aperture	F4.5 (Wide) - F6.3 (Tele)
Minimum Aperture	F22 (Wide) - F32 (Tele)
Closest Focusing Distance	0.15m/0.49ft (at focal length 18-21mm) / 0.35m/1.15ft (at focal length 40mm)
Maximum Magnification	0.28x (at focal length 21mm)
Diagonal Angle of View	100°(Wide) - 57°(Tele)
Dust and Splash Resistant	Yes*
Recommended Operating Temperature	-10°C to 40°C (14°F to 104°F)
Filter Size	φ62mm
Max. Diameter	φ67.9mm / 2.67inch
Overall Length	Approx. 40.9mm / 1.61inch (from the tip of the lens to the base side of the lens mount)
Weight	Approx. 155g / 0.34lb (excluding lens cap and lens rear cap)
Standard Accessories	Lens cap, Lens rear cap
	*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.