

## Clifton Cameras Product Specification

### Sigma 30mm f1.4 DC DN | Contemporary Lens - Canon RF Mount Full Spec

|                                 |                            |  |
|---------------------------------|----------------------------|--|
| Product Name                    |                            | SIGMA 30mm F1.4 DC DN   Contemporary   |
| Product Line                    |                            | Contemporary   |
| Lens Construction               |                            | 9 elements in 7 groups   |
|                                 | FLD Glass                  | 0  |
|                                 | ELD Glass                  | 0  |
|                                 | SLD Glass                  | 0  |
|                                 | Aspherical Elements        | 2  |
| Angle of View                   |                            | L-Mount: 50.7°<br>Sony E-mount: 50.7°<br>Micro Four Thirds mount: 39.6° Canon EF-M mount: 48.2° FUJIFILM X Mount: 50.7°<br>Nikon Z mount: 50.7°<br>Canon RF Mount: 48.2°   |
| Aperture                        | Number of Diaphragm Blades | 9  |
|                                 | Rounded Diaphragm          | ✓  |
|                                 | Minimum Aperture           | F16  |
| Minimum Focusing Distance       |                            | 30cm / 11.8in.   |
| Maximum Magnification Ratio     |                            | 1:7  |
| Filter Size                     |                            | φ52mm  |
| Dimensions (Diameter x Length*) |                            | L-Mount: φ65.4mm x 71.3mm / φ2.6in. x 2.8in.<br>Sony E-mount: φ64.8mm x 73.3mm / φ2.6in. x 2.9in.<br>Micro Four Thirds mount: φ64.8mm x 72.1mm / φ2.6in. x 2. Canon EF-M mount: φ64.8mm x 73.3mm / φ2.6in. x 2.9in. FUJIFILM X Mount: φ64.8mm x 73.6mm / φ2.6in. x 2.9in. Nikon Z mount: φ70.0mm x 75.3mm / φ2.8in. x 3.0in. Canon RF Mount: φ69.0mm x 71.3mm / φ2.7in. x 2.8in. |
|                                 |                            | *The length of a lens is measured from the front of the lens to its mount  |
| Weight                          |                            | L-Mount: 280g / 9.9oz.<br>Sony E-mount: 265g / 9.3oz.<br>Micro Four Thirds mount: 260g / 9.2oz. Canon EF-M mount: 270g / 9.5oz.<br>FUJIFILM X Mount: 275g / 9.7oz.<br>Nikon Z mount: 285g / 10.1oz.<br>Canon RF Mount: 285g / 10.1oz.  |
| Edition Number                  |                            | C016   |
| Supplied Accessories            |                            | LENS HOOD LH-586-01 FRONT CAP LCF-52 III REAR CAP LCR II   |



|                            |  |   |
|----------------------------|--|---|
| Mount / Product<br>Barcode |  | L-Mount: 00-85126-30269-6<br>Sony E-mount: 00-85126-30265-8<br>Micro Four Thirds mount: 00-85126-30263-4 Canon EF-M mount: 00-85126-30271-9 FUJIFILM X Mount: 00-85126-30275-7<br>Nikon Z mount: 00-85126-30273-3<br>Canon RF Mount: 00-85126-30272-6 |
|----------------------------|--|---|