

Canon Speedlite EL-10 Specification

[Canon Speedlite EL-10](#)

Power	Power
Guide No. (ISO100).meters	40
Zoom	
Zoom head	Auto/Manual
Focal length coverage	24-105mm
Coverage with wide panel	14mm
Auto zoom for sensor size	Yes
Flash modes	
Auto exposure control	E-TTL II / E-TTL
High speed sync (FP)	Yes
Manual / output settings	Yes -1/1 to 1/10241
Manual steps	1/3-stops
Continuous shooting priority (CP Mode)	
Continuous flashes in a burst	Maximum at full power: Approx. 652
Strobe / output settings	Not supported
Stroboscopic Frequency	Not supported
Flash-related function	
FE lock	Yes
FE memory	Yes
Flash exposure compensation	+3 stops
Flash exposure bracketing	+3 stops
Second-curtain flash sync	Yes (including wireless) ³
Modelling flash	No (supported as off-camera receiver unit only) ⁴
Modelling lamp	No
Colour temperature info communication	Yes
Wireless flash Transmitter	Yes
Transmission type	Radio only

Transmitter range	30m (approx.)5
Receiver	Yes
Max. number of Transmitters / Receivers	15/15 (16 in total of any combination)
No. of groups	5 (A/B/C/D/E)
No. of channels	Auto, 1-15
LINKED Remote Shutter Release	Yes
Flash head movement up	Up 45, 60, 75, 90 °
Down	0 °
Left	60, 75, 90, 120 and 150 °
Right	60, 75, 90, 120, 150 and 180 °
AF Assist	
AF-assist beam	Flash strobe
Number of AF points supported (infrared)	n/a
AF-assist range (at centre)	0.7-10m
Power source	Power source
Battery	4 x AA batteries
Battery level indicator	No
Minimum recycling time	Approx. 0.1-2.52,7
No. of flashes (new batteries)	210-14002
External power supply	No
Construction	
Dust and water resistance	No
Active cooling	No
Mount type supported	Multi-Function Shoe8
Misc.	
Custom Functions (C.Fn) / Personal Functions (P.Fn)	11 x C.Fn / 8 x P.Fn (plus 3 x Custom Modes (C1, C2, C3))
Flash settings from camera menus	Yes9 - On-flash Menu Direct button
External flash exposure sensor No	External flash exposure sensor No
PC terminal	No
Accessories Included	

Included	<p>Speedlite Case</p> <p>Mini Stand</p> <p>Mounting foot cover</p>
Optional	<p>Speedlite Transmitter ST-E10 (Multi-Function foot)</p> <p>Speedlite Transmitter ST-E3-RT (Ver.2) (Standard 5-pin foot)</p> <p>Color Filters SCF-E2</p> <p>Off-camera shoe cord OC-E4A</p>
Dimensions & weight	
Size (W x H x D), mm Approx. 70.6 x 116.3 x 98.3 mm	Size (W x H x D), mm Approx. 70.6 x 116.3 x 98.3 mm
Weight, grams 28	Weight, grams 287