

DJI O4 Air Unit Specifications

DJI O4 Air Unit

Item	Spec	Spec Value
Air unit	Weight	Air Unit (camera module excluded): Approx. 5.1 g
		Air Unit (camera module included) : Approx. 8.2 g*
		Antenna: Approx. 0.75 g
		<pre>^{*The lens mount is not included. With the lens mount, the weight is 9.2 grams.}</pre>
Air unit	Dimensions	Transmission Module: 30×30× 6 mm (L×W×H)
		Camera Module: 13.44×12.36×16.50 mm (L×W×H)
		Coaxial Cable: 50 mm
		3-in-1 Cable: 50 mm
		Antenna: 80 mm
Video	Operating	5.170-5.250 GHz <br< td=""></br<>
Transmission	Frequency	5.725-5.850 GHz <br< td=""></br<>
		^{Operating frequency allowed varies among countries and regions. Please refer to local laws and regulations for more information.}
Video Transmission	Transmitter Power (EIRP)	5.1 GHz: <23 dBm (CE)
		5.8 GHz:
		<30 dBm (FCC)
		<14 dBm (CE)
		< 30 dBm (SRRC)
Video Transmission	Lowest Latency	With DJI Goggles 3 and pick racing mode:
		With 1080p/100fps video transmission quality, the latency is as low as 20 ms.
		With DJI Goggles N3 and pick racing mode:

	I	
		With 1080p/100fps video transmission quality, the latency is as low as 24 ms.
		With DJI Goggles 2 or Goggles Integra:
		With 1080p/100fps video transmission quality, the video transmission latency is less than 35 ms. transmission latency is less than 35 ms.
		^{Latency data represents the minimum latency during the screen refresh process of DJI Goggles. Tested in an outdoor open environment without interference. The video transmission latency data varies with different devices.}
Video	Max Video	With DJI Goggles 3/DJI Goggles N3:
Transmission	Transmission Range	10 km (FCC),6 km (CE),6 km (SRRC)
		^{Measured in an unobstructed outdoor environment free of interference. The above data shows the farthest communication range under various standards. The actual maximum communication range during flight is limited by the flight endurance of the aircraft. Always pay attention to RTH reminders in the app during your flight.}
Video Transmission	Live View Quality	1080P@30/50/60/100fps
Video Transmission	Communication Bandwidth	Max 60 MHz
Video Transmission	Antenna	1 antenna, 1T1R
Video	Channels	Supports auto mode
Transmission		Supports manual mode:
		With DJI Goggles 3 or DJI Goggles N3:
		60 MHz: 1 channel; 40 MHz: 1 channels; 20 MHz: 3 channels; 10 MHz: 3 channel
		With DJI Goggles 2 or Goggles Integra :
		40 MHz: 1 channel; 20 MHz: 3 channels; 10 MHz: 3 channels
Video	Channels Info	FCC/SRRC/CE:
Transmission		60MHz/40 MHz :
		Channel 1: 5794.5 MHz

1001
cliftoncameras
cirredited

		0111 0011 00111 010
		20 MHz/10 MHz:
		Channel 1: 5768.5 MHz
		Channel 2: 5789.5 MHz <br< td=""></br<>
		Channel 3: 5814.5 MHz
Camera	Image Sensor	1/2-inch CMOS Sensor
Camera	Lens	FOV: 117.6°
		The equivalent focal length: 14 mm
		Aperture: f/2.8
		Focus: 0.6 m to ∞
Camera	ISO Range	100-6400 (Auto)
		100-12800 (Manual)
Camera	Video Resolution	4K(4:3): 3840 x 2880@30/50/60fps
		4K(16:9): 3840 x 2160@30/50/60fps
		1080P(4:3): 1440 x 1080@30/50/60/100/120fps
		1080P(16:9): 1920 x 1080@30/50/60/100/120fps
Camera	Video Format	MP4
Camera	Max Video Bitrate:	100 Mbps
Camera	Color Mode	Normal Mode
Camera	Camera FOV	Standard
		Wide-Angle
Camera	EIS	RockSteady 3.0+
		Stabilization function off (supports Gyroflow)
		^{When RockSteady is enabled, the shooting angle only}
		supports standard.
Hardware	Input Voltage	3.7-13.2 V
Hardware	Operating Temperature	-10° to 40° C
Storage	Built-in Storage	23GB
Storage	Supported SD Cards	Not supported
		1

Storage	Recommended microSD Cards	Not supported
Compatibility	Supported Flight Controller System	Betaflight 4.3.0 and higher versions
Compatibility	Supported DJI Goggles and Remote Controllers	DJI Goggles 3 + DJI FPV Remote Controller 3 DJI Goggles N3 + DJI FPV Remote Controller 3 DJI Goggles 2/ Goggles Integra + DJI FPV Remote Controller 2 2 2 DJI Goggles 2/ Goggles Integra + DJI FPV Remote Controller 2 2 DJI Goggles 2/ Goggles Integra + DJI FPV Remote Controller 2
		^{The flight control firmware needs to be configured to support the SBUS protocol in order to use the DJI FPV remote controller.}