

Clifton Cameras Product Specification

Leica Vario-Elmarit-SL 70-200 f/2.8 ASPH

Specifications

Number of lenses/assemblies	20/15
Position of the entrance pupil before the bayonet	70 mm: 121,3 mm 200 mm: -11,5 mm
Focus range	70 mm: 0,65 m to ∞ 200 mm: 1,00 m to ∞
Setting	Choose automatic (Autofocus) or manual mode on the camera
Smallest object field	Full-frame: 70mm: 169mm x 254mm 200mm: 124mm x 185mm
Largest scale	70 mm: 1:7,0 200 mm: 1:5,1
Setting/Function	Electronically controlled aperture, setting on the camera, half or third values can also be set
Smallest aperture	22
Bayonet	Leica L bayonet fitting with contact strip
Firmware	Lens firmware can be updated via the camera
Coating	Hydrophobe Aqua-Dura® coating on external lenses
Material	Magnesium and aluminum full-metal housing, black anodized, dust and splash water protected
Housing	The lens comes equipped with a tripod clamp and detachable tripod shoe. Only this specific tripod clamp must be used for shoots with tripod to avoid damage to the bayonet of the camera.
Filter thread	E82
Lens hood	Male bayonet for lens hood (included in the scope of delivery)
Length	Approx. 207 mm/259 mm (without/with lens hood)
Diameter	Approx. 89 mm/97 mm (without/with lens hood)
Weight	Approx. 1540 g/1670 g (without/with lens hood)