



Clifton Cameras Product Specification

[Sigma AF 10-18mm f2.8 DC DN | Contemporary Lens - Canon RF Mount](#)

Specifications

Lens Construction	13 elements in 10 groups	
	FLD Glass	3
	ELD Glass	0
	SLD Glass	1
	Aspherical Elements	4
Angle of View	L-Mount:	109.7°-76.5°
	Sony E-mount:	109.7°-76.5°
	FUJIFILM X Mount:	109.7°-76.5°
	Canon RF Mount:	106.6°-73.4°
Number of Diaphragm Blades	7	
Rounded Diaphragm	✓	
Minimum Aperture	F22	
Minimum Focusing Distance	11.6cm(W) - 19.1cm(T) / 4.6in.(W) - 7.6in.(T)	
Maximum Magnification Ratio	1:4(W) - 1:6.9(T)	
Filter Size	φ67mm	
Dimensions (Diameter x Length*)	L-Mount:	φ72.2mm x 62.0mm / φ2.8in. x 2.4in.
	Sony E-mount:	φ72.2mm x 64.0mm / φ2.8in. x 2.5in.
	FUJIFILM X Mount:	φ72.2mm x 64.3mm / φ2.8in. x 2.5in.
	Canon RF Mount:	φ72.2mm x 62.0mm / φ2.8in. x 2.4in.
	*The length of a lens is measured from the front of the lens to its mount	
Weight	L-Mount:	260g / 9.2oz.
	Sony E-mount:	255g / 9.0oz.
	FUJIFILM X Mount:	250g / 8.8oz.
	Canon RF Mount:	270g / 9.5oz.



Edition Number	C023
Supplied Accessories	LENS HOOD LH706-02
	FRONT CAP LCF-67 III
	REAR CAP LCR II