

Fujifilm Instax WIDE EVO Instant Camera - Black Specification

Instax WIDE EVO

Specifications

Camera Specifications

Image sensor:	1/3-inch CMOS with primary color filter
Number of recorded pixels:	•4608 × 3456 (WIDE ANGLE switch ON & Micro SD card inserted) •2560 × 1920 (Others)
Storage media:	Internal memory, microSD/microSDHC memory card
Storage capacity:	Approximately 45 images on the internal memory, WIDE ANGLE switch ON: approximately 280 images WIDE ANGLE switch OFF: approximately 850 images per 1 GB in microSD/microSDHC memory card
Recording method:	DCF compliant Exif Ver 2.3
Focus distance:	f = 16 mm (35mm film equivalent)
Aperture:	F2.4
Auto focus:	Single AF, Face recognition AF (on/off) (with auxiliary light)
Shooting distance:	10 cm to ∞
Shutter speed:	1/4 second to 1/8000 second (automatic switching)
Shooting sensitivity:	ISO100 to 1600 (automatic switching)
Exposure control:	Program AE
Exposure compensation:	-2.0 EV to +2.0 EV (1/3 EV step)
Metering method:	TTL 256 split metering, multi metering
White balance:	Auto, Fine, Shade, Fluorescent 1, Fluorescent 2, Fluorescent 3, Incandescent
Flash:	AUTO FLASH/FORCED FLASH/SUPPRESSED FLASH
Shooting range with flash:	Approximately 30 cm to 1.5 m



Self-timer: Approximately 2 seconds / approximately 10 seconds

Image effects: 10 lens effects with degree control functions, 10 film effects, and 6 film styles

Print Specifications

Exposure pixel count: 1600 × 1260 dots (800 × 1260 dots when printed from smartphone app)

Exposure resolution: 25 dots/mm × 12.5 dots/mm (635 × 318 dpi, 40 × 80 μm dot pitch)

12.5 dots/mm when printed from smartphone app (318 dpi, 80 μm dot pitch)

Exposure gradation: RGB gradation of 256 colors

Interface: Standard compliance: Bluetooth Ver. 5.1

Printable image format with this camera: From the camera's internal memory or microSD/microSDHC card: JPEG images taken

From a smartphone: JPEG, PNG, HEIF

Print output time: Approximately 16 seconds

Print function: Images on the internal memory and images on the memory card can be printed

Other Specifications

Smartphone app linked functions: Smartphone image print function, remote shooting function, printed image transfer function, firmware upgrade function

LCD screen: 3.5-inch TFT color LCD screen

Pixel count: Approximately 460,000 dots

External interface: USB Type-C port (for charging only)

Power supply: Lithium-ion battery (internal type)

Possible number of printed images: Approximately 100 (from full charge) The number of prints depends on the usage conditions.

Charging time: Approximately 2 to 3 hours. Charging time depends on the temperature.

Operating environment: Temperature: 5°C to 40°C

Humidity: 20% to 80% (no condensation)

Film used: FUJIFILM instant film "instax™ WIDE" (sold separately)

Weight & Dimensions

Main unit dimensions: 138.7 mm × 125 mm × 62.8 mm (excluding projecting parts)

Main unit weight: Approximately 490 g (filmcartridge, recording media, and lens cap not included.)