



HikMicro Habrok 60mm 1280px Multi-spectrum Binocular with 4K Optical & LRF Specification

[HikMicro Habrok 60mm 1280px 4K](#)

Specifications

Thermal Module

Image Sensor:	VOx Uncooled Focal Plane Arrays
Max. Resolution:	1280 × 1024
Frame Rate:	25 Hz
Pixel Interval:	12 μm
Response Waveband:	8 μm to 14 μm
NETD:	Less than 18 mK (@25°C, F# = 1.0)
Lens (Focal Length):	60 mm, F1.0
Focus Mode:	Focus Ring
Detection Range:	3100 m
Min. Focusing Distance:	3 m
Magnification:	2.6× to 26.0× (10×)
Support:	1× continuous zooming
Field of View(HxV), Degrees / m @100 m:	14.6°x8.8°/25.6 m×15.4 m

Optical Module

Image Sensor:	1.88" Progressive Scan CMOS
Max. Resolution:	3840 × 2160
Focal Length:	60 mm, F2.2
Min. Working Distance:	3 m
Focus Mode:	Focus Ring
Magnification:	5.5× to 22.0× (4×)
Field of View (HxV), Degrees/m @100 m:	7.3°x 4.1° / 12.6 m × 7.2 m
Smart IR:	Yes



cliftoncameras

IR Illuminator Wavelength: 850 nm

Viewing Range at Night: 400 m

Replaceable IR Illuminator: Yes

Image Display

Display: 0.49 inch, OLED, 1920 × 1080

Palettes: Thermal: Black Hot, White Hot, Red Hot, Fusion; Optical: Day, Night, Auto

FFC (Flat Field Correction) Mode: Auto, Manual, External Correction

Exit Pupil: 8 mm

Eye Relief: 15 mm

Diopter (Range): -5 D to +3 D

Brightness Adjustment: Yes

Tone Adjustment: Cold, warm

Contrast Adjustment: Yes

Zoom Pro: Yes

Image Pro 2.0: Yes

System

Record Video: Yes

Capture Snapshot: Yes

Audio Recording: Yes

Standby Mode: Yes

Storage: Built-in EMMC (64 GB)

PIP: Yes

Hotspot: Yes

Hot Track: Yes

Digital Magnetic Compass: Yes

GPS: Yes

Local Album: Yes

Power Supply

Battery Type: Replaceable and Rechargeable Li-ion Battery Pack



cliftoncameras

Battery Operating Time: up to 7 h (-20°C, with hotspot off, LRF and Zoom Pro on)

Type-C Power Supply: 5 V DC/2 A

Supports External Power Supply

General

Protection Level: IP67

Dimension: 152.8 mm x 81.95 mm x 231.5 mm (6.0" x 3.2" x 9.1")

Weight: 1050 g with battery pack

Working Temperature: -30°C to 55°C

Interpupillary Adjustment Range: 60 mm to 74 mm

Mounting Adapter: 1/4"-20-UNC

Laser Rangefinder

Safety Class for Laser: Class 1

Wavelength: 905 nm

Max. Measuring Range: 1000 m

Measurement Accuracy: ± 1 m

Min. Measuring Range: 10 m